

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 December 2005 (15.12.2005)

PCT

(10) International Publication Number
WO 2005/118941 A1

(51) International Patent Classification?: **D06F 39/12**

(21) International Application Number:
PCT/KR2005/001534

(22) International Filing Date: 25 May 2005 (25.05.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2004-0039501 1 June 2004 (01.06.2004) KR

(71) Applicant (for all designated States except US): LG
ELECTRONICS, INC. [KR/KR]; 20 Yoido-dong,
Youngdungpo-gu, Seoul 150-875 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): KWON, Ho-Cheol
[KR/KR]; 89-3, Sapa-dong, Changwon-si, Kyungsang-
nam-do 641-550 (KR). YIM, Il-Hyeok [KR/KR];


206-1803, Sundul-maeol, 1578-1610, Ilsan2-dong, Il-
san-gu, Goyang-si, Kyunggi-do SEOUL (KR). JUNG,
Youn-Su [KR/KR]; A-406, LG SanghwalGwan,
Gaoumjung-dong, Changwon-si, Kyungsangnam-do
641-110 (KR). SONG, Hack-Jai [KR/KR]; 706-1952,
Sogae-dong, Changwon-si, Kyungsangnam-do 641-480
(KR). KIM, Beom-Jun [KR/KR]; 203-2018, Sungwon
2nd Apt. Sangnam-dong, Changwon-si, Kyungsang-
nam-do 641-010 (KR).

(74) Agent: HAW, Yong-Noke; 8th Fl. Songchon Bldg.,
642-15, Yoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE,
KG, KM, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM,

[Continued on next page]

(54) Title: HORIZON CONTROL STRUCTURE FOR WASHING MACHINE



(57) Abstract: A horizon control structure for a washing machine is provided. The structure includes: a stopper base having a base body having a predetermined diameter, a sleeve mount hollow depressed inside of the base body and having a predetermined diameter, at least one protrusion insertion through-hole being at a distance and provided inside of the base body, and a slip preventing part provided on a bottom surface of the base body; and a leg stopper layered on the stopper base, and having a stopper body having a predetermined diameter, an insertion sleeve extended from a rear surface of the stopper body and having a predetermined diameter and length, and an insertion protrusion protruded from a rear surface of the stopper body and having a predetermined length.

WO 2005/118941 A1